



# Product Specification

Domestic Range

**B**

## 170 L Cyclone Air Indirect

Capacity	Type	Model	Installation
170L	Unvented	Internal Expansion Indirect	Floor Standing

### Descriptive Specification

- The unit is to be floor standing Cyclone pre-insulated pressurised Hot Water Cylinder
- The cylinder is to be manufactured from Duplex LDX 2101.
- The cylinder must be tested to 10 bar with a maximum operating pressure of 5 bar.
- The cylinder should have aa standing heat loss of no more than 58W.

### Constructive Specifications

Capacity	170L
Cylinder Material	Stainless Steel Duplex LDX 2101
Thermal Insulation	Polyurethane foam CFC-Free and HCFC Free
Casing	Painted Galvanised Carbon Steel DX51D
Coil Material	Stainless Steel Tube AISI 316L
Weight (empty) kg	43
Weight (full) kg	210
Max. Operating Pressure (bar)	5
Test Pressure (bar)	10
Max. Working Temperature (c)	90
Heating Elements	1 No. Incoloy Immersion
Unvented Kit Components	Inlet Control Group, Zone Valve, Cylinder Thermostat, Tundish
Coil kW Rating	20
Heat up Time (mins)	30
Product Code	TCEMVA-0170LFB
Energy Efficiency Class	B
Heat Loss (W)	58

### Dimensions

A	1285
B	540

