



Product Specification

Domestic Range

C

25090L Smart Plumb Pre-plumb

Capacity	Type	Model	Installation
250L	Unvented	Pre-plumbed Smart Plumb HG	Floor Standing

Descriptive Specification

- The unit is to be floor standing Cyclone pre-insulated pressurised Hot Water Cylinder
- The cylinder is to be manufactured from Duplex LDX 2101.
- The cylinder must be tested to 10 bar with a maximum operating pressure of 5 bar.
- The cylinder should have a standing loss of no more than 94 W

Constructive Specifications

Capacity DHW	250 L
Capacity Buffer	90 L
Cylinder Material	Stainless Steel Duplex LDX 2101
Thermal Insulation	Polyurethane foam CFC-Free and HCFC Free
Casing	Painted Galvanised Carbon Steel DX51D
Coil Material	Stainless Steel Tube AISI 316L
Weight (empty) kg	92
Weight (full) kg	432
Operating Pressure (bar)	3
Test Pressure (bar)	10
Max. Working Temperature (c)	90
Heating Elements	1. No. Incoloy Immersion
High Gain Coil Surface Area (m ²)	2.8
Heat Loss (W)	94
Product Code	TCLMVJ-25090FC
Energy Efficiency Class	C

Dimensions

A	1950
B	660
C	200
D	220
E	500
F	550
G	1520
H	1570
I	1870
J	1900
K	1950

